



1. Feature

- ▶ High Performance
- ▶ High Reliability
- ▶ RoHS Compliant

Power Divider

Part No: CPD0080M18000A02A

Date: Jan.15th.2018

Revision No: Preliminary

2. Electrical Specifications

Parameter	Specification	Remark
Frequency Range	380-18000MHz	
Insertion loss	≤1.6dB	
VSWR	≤1.70 (Input) ≤1.40 (Output)	
Amplitude Balance	≤±0.5dB	
Phase Balance	≤±5degree	
Isolation	≥12dB@350-500MHz // ≥16dB@500-18000MHz	
Average Power	20W (Forward) 1W (Reverse)	
Impedance	50Ω	

3. Mechanical Specifications

Parameter	Specifications	Remark
Dimensions	154.0x24.0x10.0mm	
Connector Type	SMA-female	
Surface Finish	Grey Painting	

4. Temperature Specifications

Parameter	Specifications	Remark
Operational Temperature	-40 to +80 °C	
Storage Temperature	-45 to +85 °C	

成都康普信源科技有限公司

Chengdu Concept Microwave Technology CO.,Ltd

No.666 ,Jinfenghuang Road , CREC Industrial Park , Jinniu District , Chengdu , China

E-mail: sales@concept-mw.com


<http://www.concept-mw.com>

Page 1 of 3

5. Outline Drawing ($\pm 0.3\text{mm}$)




CONCEPT



6. Test Curves



VSWR , Insertion Loss , AMP/Phase Balance



Isolation

