

1. Feature

- ▶ High Performance
- ▶ High Reliability
- ▶ RoHS Compliant

Power Divider

Part No: CPD02000M04000A04

Date: March.12th.2013

Revision No: Preliminary

2. Electrical Specifications

Parameter	Specification	Remark
Frequency Range	2000-4000MHz	
Insertion loss	$\leq 0.8\text{dB}$	
VSWR	≤ 1.40 (Input) ≤ 1.30 (Output)	
Amplitude Balance	$\leq \pm 0.3\text{dB}$	
Phase Balance	$\leq \pm 3\text{degree}$	
Isolation	$\geq 20\text{dB}$	
Average Power	30W (Forward) 1W (Reverse)	
Impedance	50 Ω	

3. Mechanical Specifications

Parameter	Specifications	Remark
Dimensions	56.0x50.0x10.0mm	
Connector Type	SMA-female	
Surface Finish	Grey Painting	

4. Temperature Specifications

Parameter	Specifications	Remark
Operational Temperature	-40 to +80 °C	
Storage Temperature	-45 to +85 °C	

成都康普信源科技有限公司

Chengdu Concept Microwave Technology CO.,Ltd

No.666 ,Jinfenghuang Road , CREC Industrial Park , Jinniu District , Chengdu , China

E-mail: sales@concept-mw.com

<http://www.concept-mw.com>

Page 1 of 2



5. Outline Drawing ($\pm 0.3\text{mm}$)

