



## 1. Feature

- ▶ High Performance
- ▶ High Reliability
- ▶ RoHS Compliant

Power Divider

Part No: CPD05000M18000A02

Date: Feb.20<sup>th</sup>.2020

Revision No: Preliminary

## 2. Electrical Specifications

Parameter	Specification	Remark
Frequency Range	5000-18000MHz	
Insertion Loss	≤0.5dB	
VSWR	≤1.40 (Input) ≤1.40 (Output)	
Amplitude Balance	≤±0.4dB	
Phase Balance	≤±5degree	
Isolation	≥17dB	
Average Power	20W ( Forward ) 1W (Reverse)	
Impedance	50Ω	

## 3. Mechanical Specifications

Parameter	Specifications	Remark
Dimensions	30.0x24.0x10.0mm	
Connector Type	SMA-female	
Surface Finish	Grey Painting	

## 4. Temperature Specifications

Parameter	Specifications	Remark
Operational Temperature	-40 to +80 °C	
Storage Temperature	-45 to +85 °C	

成都康普信源科技有限公司

Chengdu Concept Microwave Technology CO.,Ltd

No.666 ,Jinfenghuang Road , CREC Industrial Park , Jinniu District , Chengdu , China

E-mail: [sales@concept-mw.com](mailto:sales@concept-mw.com)


<http://www.concept-mw.com>

Page 1 of 3

5. Outline Drawing ( $\pm 0.3\text{mm}$ )



CONCEPT



## 6. Test Curves

