



1. Feature

- ▶ High Performance
- ▶ High Reliability
- ▶ RoHS Compliant

Power Divider

Part No: CPD18000M40000A02

Date: Sep.27th.2020

Revision No: Preliminary

2. Electrical Specifications

Parameter	Specification	Remark
Frequency Range	18000-40000MHz	
Insertion loss	≤1.2dB	
VSWR	≤1.60 (Input) ≤1.50(Output)	
Amplitude Balance	≤±0.40dB	
Phase Balance	≤±4degree	
Isolation	≥16dB	
Average Power	20W (Forward)	
Impedance	50Ω	

3. Mechanical Specifications

Parameter	Specifications	Remark
Dimensions	26.0x25.0x10.0mm	
Connector Type	2.92-female	
Surface Finish	Grey Painting	

4. Temperature Specifications

Parameter	Specifications	Remark
Operational Temperature	-40 to +80 °C	
Storage Temperature	-45 to +85 °C	

成都康普信源科技有限公司

Chengdu Concept Microwave Technology CO.,Ltd

No.666 ,Jinfenghuang Road , CREC Industrial Park , Jinniu District , Chengdu , China

E-mail: sales@concept-mw.com


<http://www.concept-mw.com>

Page 1 of 3

5. Outline Drawing ($\pm 0.3\text{mm}$)




CONCEPT



6. Test Curves



VSWR , Insertion Loss , AMP/Phase Balance



Isolation

